


portable UV-Vis spectrometer for gemstone analysis:


- ✓ absorption
- ✓ transmission
- ✓ luminescence



Developed by the Physics Department of the University Basel and the SSEF Swiss Gemmological Institute.

main features:

- Very light and highly sensitive spectrometer
- Large spectral range (290 - 1100 nm)
- Very fast scanning time for a spectrum (few seconds)
- Easy sample handling
- Plug-and-play with USB 2.0 in your PC or laptop
- Large spectral database of gemstones included (spectroPro)
- AvasoftBasic program included
- Protected in safety box
- **Truly portable!** All components fit in a "shoe-box"




Absorption and transmission spectrometry:

- UV transparent light diffuser for ensures the best sample illumination
- Visible (halogen) and UV light (LEDs) can be switched on/off separately
- A number of plastic rings as sample holder to prevent stray light
- UV solarization resistant fiber
- Adjustable signal/noise ratio of spectra (smoothing, averaging)
- Red warning light when bulb is broken
- Tools included for a easy bulb replacement
- Step-by-step manual how to use the instrument

Usually, recording a sample spectrum takes about 1 - 20 seconds.


How can you use it for gemstone analysis?

- Detection of copper in blue tourmaline (Paraiba-type or not?)
- Distinguish Fe-bearing rubies from Fe-free rubies (e.g. from Burma)
- Distinguish Fe-bearing emeralds from Fe-free emeralds (e.g. from Colombia)
- Detection of green dye in jadeite
- Detection of chromium in green jadeite
- Indication of origin of sapphires
- Diamond spectrum (e.g. Cape la diamonds...)
- etc...



high iron
 in emerald
 from Zambia
 (East-Africa)

low iron
 in emerald from Colombia



copper
 in Paraiba-type
 blue tourmalines !

no copper in
 light blue tourmaline !



Luminescence spectrometry:

- Metal ring with three monochromatic UV-LEDs (365 nm)
- Dark background subtracted from signal to increase signal/noise ratio

Usually, recording a luminescence spectrum takes about 1 - 100 seconds, depending on the strength of the signal.


How can you use it for gemstone analysis?

- Distinguish natural and flux synthetic red spinel
- Analyse diamond luminescence
- Analyse fluorescent fissure fillings, e.g. polymer treated jadeite (B-Jade)
- Register chromium in sapphires below XRF detection limits
- etc...



Luminescence spectra of red spinel (natural and flux grown synthetic)


SSEF mobile UV-Vis spectrometer



natural

flux melt synthetic


Luminescence spectrum of HPHT treated diamond (type Ia)



Specifications:

Spectrometer:

Avantes AvaSpec-2048 Fiber Optic Spectrometer based on the AvaBench-75 symmetrical Czerny-Turner design with 2048 pixel CCD Detector Array. The spectrometer has a fiber optic entrance connector, collimating and focusing mirror and diffractive grating enables applications in the 200-1100nm range. The AvaSpec-2048 comes with a USB2.0 interface with 16 bit AD converter and ultrafast datasampling of 900 spectra per second and datatransfer in 1.8msec.



The AvaSpec-2048 is especially suitable for low light level and high resolution applications. An optional detector coating enhances the CCD performance for the UV range and a detector collection lens offers high sensitivity.

Technical Data:

Spectrometer platform	AvaSpec-2048-USB2
Optical Bench	Symmetrical Czerny-Turner, 75 mm focal length
Wavelength range	200-1100 nm
Resolution	0.6 nm, depending on configuration
Stray light	< 0.1%
Sensitivity	20,000 (16-bit A/D) in counts/ μ W per ms integration time
Detector	CCD linear array, 2048 pixels >150 nm Deep UV detector coating Detector collection lens to enhance sensitivity, Quartz, 200-1100 nm Slit size 25 μ m
Signal/Noise	200:1
AD converter	16 bit, 2 MHz
Integration time	1.11 ms - 10 min.
Interface	USB 2.0 high speed, 480 Mbps, RS-232, 115.200 bps
Sample speed	1.1 msec /scan with on-board averaging
Data transfer speed	1.8 msec /scan
Power supply	Default USB power, 350 mA

Lamp sources:

- Vis: Halogen lamp
- UV: series of 6 LED's 300, 310, 320, 330, 340, 365 nm
- Three UV LED's 365 nm for luminescence spectra

Sample chamber:

- Aluminium tube (two parts) with adjustable aperture (depending on sample size)
- Protection cover against surrounding stray light
- Light diffuser: UV transparent quartz plate



Software:


- AvasoftBasic with manual

Dimensions, weight

ca. 400 x 300 x 150 mm, 4.7 kg
 (dimensions & total weight when stored in protection box)
 the single components are much smaller and much lighter !

Package:

- High resolution spectrometer (200-1100 nm)
- Sample chamber
- Fiber optic cable
- Light controller (transmission/luminescence)
- UV transparent light diffuser
- Additional sample holder (plastic rings)
- Avasoft software
- USB 2.0 cable
- Electrical adapter
- System operation manual
- Spare bulbs
- Bulb exchanging tools
- Protection box



Only for SSEF Spectro Pro:

- Large spectral database of gemstones
- Laptop (windows OS)
- Software pre-installation (ready-to-go and plug-and-play)
- Metallic trolley with wheels for easy travelling (only for SSEF Spectro Pro)



Pricing (VAT and shipping not included):

SSEF portable Spectro PRO	30'000.- Swiss Francs
----------------------------------	------------------------------

SSEF portable Spectro	24'000.- Swiss Francs
------------------------------	------------------------------

SSEF provides also a one day training for the instrument at SSEF laboratory or in your premises (not included in above prices. If interested, please ask for a quote)

For enquiries, please contact:

SSEF Swiss Gemmological Institut

Falknerstrasse 9
CH-4001 Basel
Switzerland

tel. +41 (0)61 262 06 40 fax. +41 (0)61 262 06 41
email: gemlab@ssef.ch website: www.ssef.ch